Co-Optimizing Speed Profiles and Signal Control Settings in Connected Vehicle Environment

Presented by: Shanjeeda Akter (Graduate Researcher) And HM Abdul Aziz, Ph.D. (Assistant Professor) Department of Civil Engineering, Kansas State University, Manhattan, KS 66506 Project Contact: azizhusain@ksu.edu (PI)

> Presented at ITS Heartland 2022 Annual Meeting (27 April 2022) Location: Lincoln, Nebraska

Signal Optimization and Speed Control



Image Source: https://www.digi.com/getattachment/blog/post/what-is-connected-vehicle-technology-and-use-cases/gettyimages-1207768535-1280x720.jpg?lang=en-us&width=1220&height=720&ext=.jpg

- Increasing market share of connected vehicles (CVs)
- C-V2X Technology Adoption
- Improving traditional signal optimization techniques
- Maximizing mobility benefits

Signal Optimization: Longest Queue First (LQF)



LQF has been implemented in different forms in the existing literature

[1] Wunderlich, Richard James. 2007. "TRACE: Tennessee Research and Creative Exchange A Longest-Queue-First Signal Scheduling Algorithm with Quality of Service Provisioning for an Isolated Intersection."

[2] Aziz, H. M.Abdul, Feng Zhu, and Satish V. Ukkusuri. 2018. "Learning-Based Traffic Signal Control Algorithms with Neighborhood Information Sharing: An Application for Sustainable Mobility." Journal of Intelligent Transportation Systems: Technology, Planning, and Operations 22 (1): 40-52. https://doi.org/10.1080/15472450.2017.1387546.

[3] Ramadán, Satria A., Endra Joelianto, and Herman Y. Sutarto. 2019. "Simulation of Traffic Control Using Vissim-." Internetworking Indonesia Journal 11 (June). https://www.researchgate.net/publication/333659545.

Speed Control Algorithm

Calculate distance to signal

4

Receive signal information (current signal state)

If there is as a green signal, calculate the minimum speed to reach the intersection before green ends and set as desired speed

If there is as a red signal, calculate the maximum speed to reach the intersection before the next green starts and set as desired speed

Speed Control

Either Fully Autonomous (SAE Level 3+ or CV-enabled with speed compliance

SPaT Message

Distance to signal

Image Source: https://www.thecarconnection.com/news/1080042_vehicle-to-infrastructure-technology-on-the-road-in-germany





Data: AM Peak Hour; Existing signal timing plan

- Driving Behavior: Calibration Connected Vehicle (CV) technologies
 - **Vissim COM Interface**
 - Signal controllers and vehicles can communicate and share data
- Data Collection













Location: Merriam, KS

Intersection of Santa Fe Dr and Foster St with Shawnee Mission Pkwy









For Shawnee Mission Pkwy Major Approach Through Traffic

Avg Delay was reduced to 1/5 of previous delay

Avg Stopped Delay was reduced by 95% from previous stopped delay

Avg No. of Stops was reduced by about 57%

Max Queue Length became 2/5

Results - LQF Algorithm: No. of Stops

Improvement in No. of Stops due to LQF Algorithm



Field Volume = 10% Higher Volume = 20% Higher Volume

Results - LQF Algorithm



Maximum Queue Length (m) for Fixed Time Signal

	Major Through	Major Left	SB	NB
Field Volume	262.09	28.54	82.51	84.87
10% Increased Volume	480.49	28.29	78.71	83.04
20% Increased Volume	504.74	22.47	82.52	84.87
Maximum Queue Length (m) for LQF Algorithm				
	Major Through	Major Left	SB	NB
Field Volume	102.79	103.24	73.87	84.08
10% Increased Volume	220.55	220.99	76.56	83.37
20% Increased Volume	502.82	503.26	76.79	84.42
Changes in Maximum Queue Length (Percentage)				
	Major Through	Major Left	SB	NB
Field Volume	60 78 or	Queue exceeds left turn	10 //70/-	0.930/2

Results - Dynamic Speed Algorithm



For Shawnee Mission Pkwy Major Approach Through Traffic

Avg Delay was reduced to 2/5 of previous delay

Avg Stopped Delay was reduced by 94% to 99% from previous stopped delay

Avg No. of Stops was reduced by about 73% to 80%

Results - Speed Control Algorithm

Improvement in Stopped Delay (sec/veh) due to Speed Control Algorithm



Results - Speed Control Algorithm



Limitations and Ongoing Works

Limitations:

- Consideration for all red time
- Poor performance at high demand volume
- Algorithm works for fixed time signal control
- Ongoing Works:
 - Development of Connected-Vehicle based advanced algorithms
 - Coordinating dynamic speed control with variable signal timing settings
 - Market share of CVs
 - Prediction model
 - **Environmental impact**



Acknowledgments:

E-mail: shanjeeda@ksu.edu

This work is partially funded by the KSU Foundation and BHC Inc.

We are also grateful to MARC MPO for providing us the data for the testbed in Merriam, KS